

CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 60000001096 Date of first issue: 09/06/2017

SECTION 1. IDENTIFICATION

Product name : CYCLO DIESEL FUEL INJ CLNR 12/32OZ

Product code : C21

Manufacture or supplier's details

Company Name of Supplier : Niteo Products, LLC

Address : 5949 Sherry Ln. Suite 540 Dallas, TX 7225

Email : EHS@niteoproducts.com
Phone Number : +1 (844) 696-4836
Australian Importer : Cyclo Australia

Address : 2/19 Technology Circuit Hallam 3803

Email : sales@cycloaustralia.com

Phone Number : +61 3 9702 4314

Website : www.cycloaustralia.com.au

Poison Information : Ph 13 11 26

Recommended use of the chemical and restrictions on use

Recommended use : FUEL INJ CLEANER

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 1B

Specific target organ toxicity

- single exposure

Category 3 (Central nervous system)

Specific target organ toxicity

- repeated exposure

: Category 2 (Liver, thymus, Bone marrow)

Aspiration hazard : Category 1



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 600000001096 Date of first issue: 09/06/2017

GHS label elements

Hazard pictograms







Signal word : Danger

Hazard statements : Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficulties

if inhaled.

May cause drowsiness or dizziness.

Suspected of causing cancer.

May damage fertility or the unborn child.

May cause damage to organs (Liver, thymus, Bone marrow)

through prolonged or repeated exposure.

Precautionary statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Keep away from heat/sparks/open flames/hot surfaces. No

smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the

workplace.

Wear protective gloves/ protective clothing/ eye protection/ face

protection.

In case of inadequate ventilation wear respiratory protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/ attention.

Do NOT induce vomiting.

If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 600000001096 Date of first issue: 09/06/2017

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

olant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Diesel fuel no. 2	68476-34-6	>= 70 - < 90
Kerosene	8008-20-6	>= 30 - < 50
Solvent naphtha (petroleum)	64742-94-5	>= 5 - < 10
Alkanes, C10-C20 branched and linear	928771-01-1	>= 1 - < 5
Naphthalene	91-20-3	>= 1 - < 5
Phenol, dodecyl- branched	210555-94-5	>= 0.1 - < 1
Ethylenediamine; 1,2-diaminoethane	107-15-3	>= 0.1 - < 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

Call a physician or poison control centre immediately.

If unconscious, place in recovery position and seek medical

advice.

Keep patient warm and at rest. If symptoms persist, call a physician.

In case of skin contact : If on clothes, remove clothes.

Remove contaminated clothing. If irritation develops, get med-

ical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If swallowed : Obtain medical attention.

Do NOT induce vomiting.



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

02/27/2024 60000001096 Date of first issue: 09/06/2017 2.0

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delaved

Inhalation or ingestion of high levels of this material (or a component) may cause a hemolytic reaction. Complications of acute intravascular hemolysis include anemia. leukocytosis. fever, hemoglobinuria, jaundice, renal insufficiency, and

sometimes disturbances in liver function.

Fats, for example, baby oil on the skin or ingested oil, facilitate

absorption of naphthalene.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause drowsiness or dizziness. Suspected of causing cancer.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated

exposure.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Dry chemical

Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

Carbon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information Do not use a solid water stream as it may scatter and spread

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 600000001096 Date of first issue: 09/06/2017

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation.

Avoid breathing dust.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Evacuate personnel to safe areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against : fire and explosion

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vanours)

(which might cause ignition of organic vapours). Electrically bond and ground all containers, personnel and

equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protec-

tion Association document NFPA 77.

Keep away from open flames, hot surfaces and sources of

ignition.

Use only explosion-proof equipment.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling

Open drum carefully as content may be under pressure.

Avoid formation of aerosol.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Take precautionary measures against static discharges.

Avoid contact with skin and eyes.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 600000001096 Date of first issue: 09/06/2017

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

No smoking.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diesel fuel no. 2	68476-34-6	TWA (Inhal- able fraction and vapor)	100 mg/m3 ACGIH (total hydrocarbons)	
Kerosene	8008-20-6	TWA	100 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0
Solvent naphtha (petroleum)	64742-94-5	TWA	200 mg/m3 ACGIH (total hydrocarbon vapor)	
Naphthalene	91-20-3	TWA	10 ppm	ACGIH
		TWA	10 ppm 50 mg/m3	NIOSH REL
		ST	15 ppm 75 mg/m3	NIOSH REL
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		TWA	10 ppm 50 mg/m3	OSHA P0
		STEL	15 ppm 75 mg/m3	OSHA P0
Ethylenediamine; 1,2-diaminoethane	107-15-3	TWA	10 ppm	ACGIH
		TWA	10 ppm 25 mg/m3	NIOSH REL
		TWA	10 ppm 25 mg/m3	OSHA Z-1
		TWA	10 ppm 25 mg/m3	OSHA P0

Hazardous components without workplace control parameters

Components	CAS-No.
Alkanes, C10-C20 branched	928771-01-1
and linear	
Phenol, dodecyl- branched	210555-94-5



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 60000001096 Date of first issue: 09/06/2017

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.



Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

Hand protection



Remarks : Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection

Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Flame-resistant clothing

Safety shoes



Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not smoke. When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : light red

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : not determined

Boiling point/boiling range : 154 - 366 °C

Flash point : 58 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 60000001096 Date of first issue: 09/06/2017

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

: No data available

Lower explosion limit / Lower

flammability limit

not determined

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.8504 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Molecular weight : No data available

VOC % By Weight : 10 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact Skin contact Ingestion



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 60000001096 Date of first issue: 09/06/2017

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 4.09 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

Diesel fuel no. 2:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male and female): 4.1 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 4,300 mg/kg

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Kerosene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 420

Acute inhalation toxicity : LC50 (Rat): > 5.8 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Solvent naphtha (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 3,800 mg/m3

Exposure time: 4 h
Test atmosphere: vapour

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 60000001096 Date of first issue: 09/06/2017

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Alkanes, C10-C20 branched and linear:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after

short term inhalation.

Naphthalene:

Acute oral toxicity : LD50 (Mouse, male): 533 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.4 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,500 mg/kg

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Phenol, dodecyl- branched:

Acute oral toxicity : LD50 (Rat): 2,100 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,000 mg/kg

Ethylenediamine; 1,2-diaminoethane:

Acute oral toxicity : LD50 (Rabbit): 866 mg/kg

Acute inhalation toxicity : LC50 (Rat): 14700 mg/m3

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 560 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Diesel fuel no. 2:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

Kerosene:

Result: Irritating to skin.



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 60000001096 Date of first issue: 09/06/2017

Solvent naphtha (petroleum):

Result: Mild skin irritation

Naphthalene:

Result: Possibly irritating to skin

Phenol, dodecyl- branched:

Assessment: Causes burns.

Ethylenediamine; 1,2-diaminoethane:

Assessment: Causes burns.

Remarks: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Diesel fuel no. 2:

Species: Rabbit

Result: Possibly irritating to eyes Method: OECD Test Guideline 405

Kerosene:

Result: Possibly irritating to eyes

Solvent naphtha (petroleum):

Result: Possibly irritating to eyes

Naphthalene:

Result: Possibly irritating to eyes

Phenol, dodecyl- branched:

Assessment: Risk of serious damage to eyes.

Remarks: Causes eye burns.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 60000001096 Date of first issue: 09/06/2017

Product:

Remarks: May cause allergic skin reaction.

Components:

Diesel fuel no. 2:

Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Method: OECD Test Guideline 406

Ethylenediamine; 1,2-diaminoethane:

Exposure routes: Inhalation

Assessment: May cause sensitisation by inhalation.

Exposure routes: Dermal

Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Components:

Diesel fuel no. 2:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse mu-

tation assay) Result: positive

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:

Diesel fuel no. 2:

Carcinogenicity - Assess-

ment

Limited evidence of carcinogenicity in animal studies

Naphthalene:

Carcinogenicity - Assess-

ment

Limited evidence of carcinogenicity in inhalation studies with

animals.

IARC Group 2B: Possibly carcinogenic to humans

Naphthalene 91-20-3

OSHANo component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 60000001096 Date of first issue: 09/06/2017

NTP Reasonably anticipated to be a human carcinogen

Naphthalene 91-20-3

Reproductive toxicity

May damage fertility or the unborn child.

Components:

Phenol, dodecyl- branched:

Reproductive toxicity - Assessment

Clear evidence of adverse effects on sexual function and fertil-

ity, and/or on development, based on animal experiments

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Kerosene:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs (Liver, thymus, Bone marrow) through prolonged or repeated exposure.

Components:

Diesel fuel no. 2:

Target Organs: Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

Target Organs: thymus

Assessment: May cause damage to organs through prolonged or repeated exposure.

Target Organs: Bone marrow

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Diesel fuel no. 2:

May be fatal if swallowed and enters airways.

Kerosene:

May be fatal if swallowed and enters airways.

Solvent naphtha (petroleum):

May be fatal if swallowed and enters airways.



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version **Revision Date:** SDS Number: Date of last issue: -

02/27/2024 60000001096 Date of first issue: 09/06/2017 2.0

Alkanes, C10-C20 branched and linear:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vom-

iting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No. UN 1268

Proper shipping name Petroleum distillates, n.o.s.

Class 3 Packing group Ш Labels 3 Packing instruction (cargo 366

aircraft)

Packing instruction 355

(passenger aircraft)

IMDG-Code

UN 1268 **UN** number

PETROLEUM DISTILLATES, N.O.S. Proper shipping name

Class 3 Ш Packing group





CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 60000001096 Date of first issue: 09/06/2017

Labels : 3

EmS Code : F-E, S-E Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1268

Proper shipping name : Petroleum distillates, n.o.s.

Class : 3
Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : no





SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Benzene	71-43-2	10	10 (D018)
Naphthalene	91-20-3	100	3465

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Ethylenediamine; 1,2-	107-15-3	5000	*
diaminoethane			

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation Respiratory or skin sensitisation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard Reproductive toxicity

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Naphthalene 91-20-3 >= 1 - < 5 %



CYCLO® DIESEL FUEL INJECTOR CLEANER

Version Revision Date: SDS Number: Date of last issue: -

2.0 02/27/2024 60000001096 Date of first issue: 09/06/2017


California Prop. 65

WARNING: This product can expose you to chemicals including Naphthalene, Benzene, Formal-dehyde, which is/are known to the State of California to cause cancer, and Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 02/27/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN