

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: - Date of first issue: 08/28/2017

SECTION 1. IDENTIFICATION

Product name : CYCLO RUBBERIZED AERO UNDERCOAT 12/16FOZ

Product code : C35

Manufacture or supplier's details

Company Name of Supplier : Niteo Products, LLC
Address : 5949 Sherry Ln. Suite 540 Dallas, TX 7225
Email : EHS@niteoproducts.com
Phone Number : +1 (844) 696-4836
Australian Importer : Cyclo Australia
Address : 2/19 Technology Circuit Hallam 3803
Email : sales@cycloaustralia.com
Phone Number : +61 3 9702 4314
Website : www.cycloaustralia.com.au
Poison Information : Ph 13 11 26

Recommended use of the chemical and restrictions on use

Recommended use : UNDERCOATS

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable aerosols : Category 1

Skin irritation : Category 2

Eye irritation : Category 2A

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision))

Aspiration hazard : Category 1

GHS label elements

SAFETY DATA SHEET

CYCLO® RUBBERIZED AEROSOL UNDERCOAT



| | | | |
|----------------|------------------------------|-----------------------------|--|
| Version 1.1 | Revision Date: 01/07/2021 | SDS Number: 600000001239 | Date of last issue: - Date of first issue: 08/28/2017 |
|----------------|------------------------------|-----------------------------|--|

| | | |
|--------------------------|---|--|
| Hazard pictograms | : | |
| Signal word | : | Danger |
| Hazard statements | : | Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging the unborn child. May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled. |
| Precautionary statements | : | <p>Prevention:</p> <p>Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>Response:</p> <p>IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.</p> <p>Storage:</p> <p>Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.</p> <p>Disposal:</p> <p>Dispose of contents/ container to an approved waste disposal plant.</p> |

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

| | | | |
|----------------|------------------------------|-----------------------------|--|
| Version 1.1 | Revision Date: 01/07/2021 | SDS Number: 600000001239 | Date of last issue: - Date of first issue: 08/28/2017 |
|----------------|------------------------------|-----------------------------|--|

Other hazards

None known.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration (% w/w) |
|----------------|-----------|-----------------------|
| Limestone | 1317-65-3 | >= 30 - < 50 |
| Toluene | 108-88-3 | >= 10 - < 20 |
| Methyl acetate | 79-20-9 | >= 10 - < 20 |
| Acetone | 67-64-1 | >= 5 - < 10 |
| Carbon Black | 1333-86-4 | >= 0.1 - < 1 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and : May be fatal if swallowed and enters airways.
Causes skin irritation.

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

| | | | |
|----------------|------------------------------|-----------------------------|--|
| Version 1.1 | Revision Date: 01/07/2021 | SDS Number: 600000001239 | Date of last issue: - Date of first issue: 08/28/2017 |
|----------------|------------------------------|-----------------------------|--|

| | |
|---------|--|
| delayed | Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled. |
|---------|--|

SECTION 5. FIREFIGHTING MEASURES

| | |
|---|--|
| Suitable extinguishing media | : Water spray Carbon dioxide (CO2) Dry chemical Alcohol-resistant foam |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire-fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon oxides |
| Specific extinguishing methods | : Product is compatible with standard fire-fighting agents. |
| Further information | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : In the event of fire, wear self-contained breathing apparatus. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation. Avoid breathing dust. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Evacuate personnel to safe areas. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. |
| Environmental precautions | : Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. |

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: - Date of first issue: 08/28/2017

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment. Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure. Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe vapours/dust. Do not smoke. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Dispose of rinse water in accordance with local and national regulations. Container hazardous when empty. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|-----------|--------------------------------|--|-----------|
| Limestone | 1317-65-3 | TWA (total dust) | 15 mg/m ³ | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m ³ | OSHA Z-1 |
| | | TWA (Total dust) | 15 mg/m ³ | OSHA P0 |
| | | TWA (respirable dust fraction) | 5 mg/m ³ | OSHA P0 |
| | | TWA (Respirable) | 5 mg/m ³ (Calcium car- | NIOSH REL |

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021

SDS Number: 600000001239

Date of last issue: -
Date of first issue: 08/28/2017

| | | | | |
|----------------|-----------|-------------------------------|--------------------------------------|-----------|
| | | | bonate) | |
| | | TWA (total) | 10 mg/m3 (Calcium car- bonate) | NIOSH REL |
| Toluene | 108-88-3 | TWA | 20 ppm | ACGIH |
| | | TWA | 100 ppm 375 mg/m3 | NIOSH REL |
| | | ST | 150 ppm 560 mg/m3 | NIOSH REL |
| | | TWA | 200 ppm | OSHA Z-2 |
| | | CEIL | 300 ppm | OSHA Z-2 |
| | | Peak | 500 ppm (10 minutes) | OSHA Z-2 |
| | | TWA | 100 ppm 375 mg/m3 | OSHA P0 |
| | | STEL | 150 ppm 560 mg/m3 | OSHA P0 |
| Methyl acetate | 79-20-9 | TWA | 200 ppm | ACGIH |
| | | STEL | 250 ppm | ACGIH |
| | | TWA | 200 ppm 610 mg/m3 | NIOSH REL |
| | | ST | 250 ppm 760 mg/m3 | NIOSH REL |
| | | TWA | 200 ppm 610 mg/m3 | OSHA Z-1 |
| | | TWA | 200 ppm 610 mg/m3 | OSHA P0 |
| | | STEL | 250 ppm 760 mg/m3 | OSHA P0 |
| Acetone | 67-64-1 | TWA | 250 ppm | ACGIH |
| | | STEL | 500 ppm | ACGIH |
| | | TWA | 250 ppm 590 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 2,400 mg/m3 | OSHA Z-1 |
| | | TWA | 750 ppm 1,800 mg/m3 | OSHA P0 |
| | | STEL | 1,000 ppm 2,400 mg/m3 | OSHA P0 |
| Carbon Black | 1333-86-4 | TWA (Inhal- able fraction) | 3 mg/m3 | ACGIH |
| | | TWA | 3.5 mg/m3 | NIOSH REL |
| | | TWA | 3.5 mg/m3 | OSHA Z-1 |
| | | TWA | 3.5 mg/m3 | OSHA P0 |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sam- pling time | Permissible concentra- tion | Basis |
|------------|----------|--------------------|---------------------|--|--------------------------------|--------------|
| Toluene | 108-88-3 | Toluene | In blood | Prior to last shift of work- week | 0.02 mg/l | ACGIH BEI |

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

| | | | |
|----------------|------------------------------|-----------------------------|--|
| Version 1.1 | Revision Date: 01/07/2021 | SDS Number: 600000001239 | Date of last issue: - Date of first issue: 08/28/2017 |
|----------------|------------------------------|-----------------------------|--|

| | | | | | | |
|---------|---------|----------|-------|--|---------------------|-----------|
| | | Toluene | Urine | End of shift (As soon as possible after exposure ceases) | 0.03 mg/l | ACGIH BEI |
| | | o-Cresol | Urine | End of shift (As soon as possible after exposure ceases) | 0.3 mg/g Creatinine | ACGIH BEI |
| Acetone | 67-64-1 | Acetone | Urine | End of shift (As soon as possible after exposure ceases) | 25 mg/l | ACGIH BEI |

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment



Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
In the case of dust or aerosol formation use respirator with an approved filter.



Hand protection

Remarks



Eye protection



Skin and body protection



Hygiene measures

: Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

: Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

: Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Flame-resistant clothing
Safety shoes

: Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SAFETY DATA SHEET

CYCLO® RUBBERIZED AEROSOL UNDERCOAT



Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: - Date of first issue: 08/28/2017

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol
Colour : black
Odour : solvent-like
Odour Threshold : No data available
pH : No data available
Melting point/range : No data available
Boiling point/boiling range : No data available
Flash point : -104.45 °C
Method: closed cup
Evaporation rate : No data available
Flammability (solid, gas) : No data available
Self-ignition : No data available
Upper explosion limit / Upper flammability limit : No data available
Lower explosion limit / Lower flammability limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 1.122 g/cm3
Solubility(ies)
Water solubility : negligible
Partition coefficient: n-octanol/water : No data available
Decomposition temperature : No data available
Viscosity
Viscosity, kinematic : No data available
Molecular weight : No data available
VOC % By Weight : 37.48 %

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET

CYCLO® RUBBERIZED AEROSOL UNDERCOAT



Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: - Date of first issue: 08/28/2017

| | |
|------------------------------------|---|
| Reactivity | : No decomposition if stored and applied as directed. |
| Chemical stability | : No decomposition if stored and applied as directed. |
| Possibility of hazardous reactions | : No decomposition if stored and applied as directed. Vapours may form explosive mixture with air. |
| Conditions to avoid | : Heat, flames and sparks. |
| Incompatible materials | : Strong oxidizing agents |
| Hazardous decomposition products | : Carbon oxides |

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Eye contact
Skin contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

| | |
|---------------------------|---|
| Acute oral toxicity | : Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method |
| Acute inhalation toxicity | : Acute toxicity estimate: 129.91 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method |
| Acute dermal toxicity | : Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method |

Components:

Limestone:

Acute oral toxicity : LD50 (Rat): 6,450 mg/kg

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, males): 25.7 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,124 mg/kg

Methyl acetate:

Acute oral toxicity : LD50 (Rat, male): 6,482 mg/kg

SAFETY DATA SHEET

CYCLO® RUBBERIZED AEROSOL UNDERCOAT



| | | | |
|----------------|------------------------------|-----------------------------|--|
| Version 1.1 | Revision Date: 01/07/2021 | SDS Number: 600000001239 | Date of last issue: - Date of first issue: 08/28/2017 |
|----------------|------------------------------|-----------------------------|--|

Method: OECD Test Guideline 401

- Acute inhalation toxicity : LC50 (Rabbit): > 49.2 mg/l
Exposure time: 4 h
Test atmosphere: vapour
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Acetone:

- Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg
- Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour
- Acute dermal toxicity : LD50 (Rabbit): > 7,426 mg/kg

Carbon Black:

- Acute oral toxicity : LD50 (Rat): 8,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Limestone:

Result: Possibly irritating to skin

Toluene:

Result: Irritating to skin.

Methyl acetate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Possibly irritating to skin

Acetone:

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

Carbon Black:

Species: Rabbit

SAFETY DATA SHEET

CYCLO® RUBBERIZED AEROSOL UNDERCOAT



Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: - Date of first issue: 08/28/2017

Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Limestone:

Result: Possibly irritating to eyes

Toluene:

Result: Irritating to eyes.

Methyl acetate:

Species: Rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

Acetone:

Result: Irritating to eyes.

Assessment: Irritating to eyes.

Carbon Black:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Toluene:

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Not a skin sensitizer.

Methyl acetate:

Assessment: Does not cause skin sensitisation.

Carbon Black:

Test Type: Buehler Test

SAFETY DATA SHEET

CYCLO® RUBBERIZED AEROSOL UNDERCOAT



Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: - Date of first issue: 08/28/2017

Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

Methyl acetate:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects
Genotoxicity in vivo : Test Type: Micronucleus test
Species: Rat
Method: OECD Test Guideline 474
Result: negative

Carbon Black:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:

Carbon Black:

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

IARC

Group 2B: Possibly carcinogenic to humans

Carbon Black 1333-86-4

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Toluene:

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: - Date of first issue: 08/28/2017

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Toluene:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

Methyl acetate:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Acetone:

Exposure routes: Inhalation

Target Organs: Nervous system

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

Components:

Toluene:

Exposure routes: Inhalation

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Methyl acetate:

Species: Rat

NOAEL: 1.05 mg/l

Application Route: Inhalation

Test atmosphere: dust/mist

Exposure time: N11.00322320

Method: OECD Test Guideline 412

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Toluene:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: - Date of first issue: 08/28/2017

Acetone:

May be harmful if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203



IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: - Date of first issue: 08/28/2017

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.



National Regulations

49 CFR

UN/ID/NA number : UN 1950
Proper shipping name : Aerosols

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
ERG Code : 126
Marine pollutant : no



SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|--------------|-----------|--------------------|-----------------------------|
| Toluene | 108-88-3 | 100 | 100 (F005) |
| Acetone | 67-64-1 | 100 | 100 (F003) |
| Methanol | 67-56-1 | 100 | 100 (F003) |
| Xylene | 1330-20-7 | 100 | 100 (F003) |
| Ethylbenzene | 100-41-4 | 100 | 100 (F003) |
| Benzene | 71-43-2 | 10 | 10 (D018) |
| Toluene | 108-88-3 | 1000 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Carcinogenicity

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Toluene 108-88-3 >= 10 - < 20 %

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version Revision Date: SDS Number: Date of last issue: -
1.1 01/07/2021 600000001239 Date of first issue: 08/28/2017

California Prop. 65


WARNING: This product can expose you to chemicals including Carbon Black, Silica, crystalline Quartz, Ethylbenzene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Methanol, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:

Flammability



Special hazard.

Revision Date : 01/07/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN