

SAFETY DATA SHEET



Pyroil™ POWER STEERING FLUID FOR HONDA & ACURA ENGINES™ Trademark, Niteo Products, LLC

Version	Revision Date:	SDS Number:	Date of last issue: 03/06/2019
3.0	07/25/2019	600000001750	Date of first issue: 03/04/2019

SECTION 1. IDENTIFICATION

Product name : PYROIL HONDA PSF 12/12 FOZ

Product code : PYHPS12

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Phone number : From AUS 0011 1 (800) 843-713

Fax number : From AUS 0011 1 (561) 745-3867

Emergency Contact : First Aid Emergency 0011 1 (321) 906-6194

Distributor info: : Unit 2/19 Technology Circuit, Hallam VIC 3803 03 9702 4314

The Poison Information : Ph:13 11 26
Center Australia

Recommended use of the chemical and restrictions on use

Recommended use : POWER STEERING FLUID

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : May cause an allergic skin reaction.

Precautionary statements : **Prevention:**
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves.

SAFETY DATA SHEET



Pyroil™ POWER STEERING FLUID FOR HONDA & ACURA ENGINES™ Trademark, Niteo Products, LLC

Version 3.0 Revision Date: 07/25/2019 SDS Number: 600000001750 Date of last issue: 03/06/2019
Date of first issue: 03/04/2019

Response:

IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/ attention.
Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum)	64742-54-7	$\geq 50 - < 70$
Distillates (petroleum)	64742-55-8	$\geq 1 - < 5$
Mineral Oil (described by one of more of following CAS No : 64742-54-7, 64742-65-0, 64742-55-8 and 64742-56-9)	Not Assigned	$\geq 1 - < 5$
Substituted hydrocarbyl sulfide	Not Assigned	$\geq 1 - < 5$

Any concentration shown as a range is to protect confidentiality or is due to batch variation. If no CAS number is identified, the component is considered trade secret.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

SAFETY DATA SHEET



Pyroil™ POWER STEERING FLUID FOR HONDA & ACURA ENGINES™ Trademark, Niteo Products, LLC

Version	Revision Date:	SDS Number:	Date of last issue: 03/06/2019
3.0	07/25/2019	600000001750	Date of first issue: 03/04/2019

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid breathing dust.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET



Pyroil™ POWER STEERING FLUID FOR HONDA & ACURA ENGINES™ Trademark, Niteo Products, LLC

Version 3.0 Revision Date: 07/25/2019 SDS Number: 600000001750 Date of last issue: 03/06/2019
Date of first issue: 03/04/2019

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Avoid contact with skin and eyes.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum)	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum)	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Mineral Oil (described by one of more of following CAS No : 64742-54-7, 64742-65-0, 64742-55-8 and 64742-56-9)	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1

SAFETY DATA SHEET



Pyroil™ POWER STEERING FLUID FOR HONDA & ACURA ENGINES™ Trademark, Niteo Products, LLC

Version 3.0 Revision Date: 07/25/2019 SDS Number: 600000001750 Date of last issue: 03/06/2019
Date of first issue: 03/04/2019

		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Hazardous components without workplace control parameters

Components	CAS-No.
Substituted hydrocarbyl sulfide	Not Assigned

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : not determined

Odour : not determined

Odour Threshold : not determined

pH : not determined

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

SAFETY DATA SHEET



Pyroil™ POWER STEERING FLUID FOR HONDA & ACURA ENGINES™ Trademark, Niteo Products, LLC

Version 3.0	Revision Date: 07/25/2019	SDS Number: 600000001750	Date of last issue: 03/06/2019 Date of first issue: 03/04/2019
----------------	------------------------------	-----------------------------	---

Flash point	:	153 °C Value for Component
Evaporation rate	:	not determined
Flammability (solid, gas)	:	No data available
Self-ignition	:	not determined
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Vapour pressure	:	not determined
Relative vapour density	:	not determined
Density	:	0.8518 g/cm3
Solubility(ies) Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not determined
Decomposition temperature	:	not determined
Viscosity Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Hazardous polymerisation does not occur.
Conditions to avoid	:	No data available
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	Carbon oxides

**Pyroil™ POWER STEERING FLUID FOR
HONDA & ACURA ENGINES™ Trademark,
Niteo Products, LLC**

Version	Revision Date:	SDS Number:	Date of last issue: 03/06/2019
3.0	07/25/2019	600000001750	Date of first issue: 03/04/2019

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Eye contact
Skin contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity	: Acute toxicity estimate: 17.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

Components:**Distillates (petroleum):**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Information given is based on data obtained from similar substances.
Acute inhalation toxicity	: LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: No adverse effect has been observed in acute inhalation toxicity tests. Remarks: Information given is based on data obtained from similar substances.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402 Remarks: Information given is based on data obtained from similar substances.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:**Distillates (petroleum):**

SAFETY DATA SHEET



Pyroil™ POWER STEERING FLUID FOR HONDA & ACURA ENGINES™ Trademark, Niteo Products, LLC

Version	Revision Date:	SDS Number:	Date of last issue: 03/06/2019
3.0	07/25/2019	600000001750	Date of first issue: 03/04/2019

Result: No skin irritation

Remarks: Information given is based on data obtained from similar substances.

Distillates (petroleum):

Result: Possibly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.
Unlikely to cause eye irritation or injury.

Components:

Distillates (petroleum):

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Remarks: Information given is based on data obtained from similar substances.

Distillates (petroleum):

Result: Possibly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks: May cause allergic skin reaction.

Components:

Distillates (petroleum):

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Not a skin sensitizer.

Remarks: Information given is based on data obtained from similar substances.

Substituted hydrocarbyl sulfide:

Result: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET



Pyroil™ POWER STEERING FLUID FOR HONDA & ACURA ENGINES™ Trademark, Niteo Products, LLC

Version	Revision Date:	SDS Number:	Date of last issue: 03/06/2019
3.0	07/25/2019	600000001750	Date of first issue: 03/04/2019

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum):

Carcinogenicity - Assessment : Not classifiable as a human carcinogen., Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Mineral Oil (described by one of more of following CAS No : 64742-54-7, 64742-65-0, 64742-55-8 and 64742-56-9):

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SAFETY DATA SHEET



Pyroil™ POWER STEERING FLUID FOR HONDA & ACURA ENGINES™ Trademark, Niteo Products, LLC

Version	Revision Date:	SDS Number:	Date of last issue: 03/06/2019
3.0	07/25/2019	600000001750	Date of first issue: 03/04/2019

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Butanol normal	71-36-3	100	100 (F003)
Toluene	108-88-3	100	100 (F005)
Benzene	71-43-2	10	10 (D018)
Phosphoric acid	7664-38-2	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SAFETY DATA SHEET



Pyroil™ POWER STEERING FLUID FOR HONDA & ACURA ENGINES™ Trademark, Niteo Products, LLC

Version 3.0 Revision Date: 07/25/2019 SDS Number: 600000001750 Date of last issue: 03/06/2019
Date of first issue: 03/04/2019

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Sulfur dioxide	7446-09-5	500	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitisation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


California Prop. 65

WARNING: This product can expose you to chemicals including Trimethyl phosphate, Ethyl Acrylate, Naphthalene, Benzene, which is/are known to the State of California to cause cancer, and Sulfur dioxide, Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 07/25/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET



Pyroil™ POWER STEERING FLUID FOR HONDA & ACURA ENGINES™ Trademark, Niteo Products, LLC

Version	Revision Date:	SDS Number:	Date of last issue: 03/06/2019
3.0	07/25/2019	600000001750	Date of first issue: 03/04/2019

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN